Neutralize Tank Cleaner®

An emulsifiable concentrate containing a proprietary blend of tank mix agents.

The (COSHH) Control of Substances Hazardous to Health Regulations may apply to the use of this product at work.

SAFETY PRECAUTIONS
Operator protection
Engineering control of operator exposure must be used where reasonably practicable in addition to the following personal protective equipment:
WEAR SUITABLE PROTECTIVE CLOTHING (COVERALLS), SUITABLE PROTECTIVE GLOVES AND FACE PROTECTION (FACESHIELD) when handling the concentrate.
AVOID CONTACT WITH SKIN AND EYES.
WASH HANDS AND EXPOSED SKIN before meals and after work.
WHEN USING DO NOT EAT, DRINK OR SMOKE.

Environmental protection
Do not contaminate surface waters or ditches with chemical or used container.

Storage and disposal
KEEP AWAY FROM FOOD, DRINK AND ANIMAL FEEDINGSTUFFS.
KEEP OUT OF REACH OF CHILDREN.
KEEP IN ORIGINAL CONTAINER, tightly closed, in a safe place.
DO NOT RE-USE CONTAINER for any purpose.
Protect from frost.

DIRECTIONS FOR USE
Neutralize Tank Cleaner is a Spray Tank Cleaner that can be used to clean and decontaminate tanks, spray lines and transfer pumps.

Neutralize Tank Cleaner was developed to handle difficult to clean agricultural chemicals, sticky formulations and sulfonylurea herbicides.

Neutralize Tank Cleaner is supported by BASF for the following herbicides:
ATLANTIS, LEXUS, BROADWAY STAR, ALLY MAX SX, TITUS AND EAGLE.
For a complete list of supported herbicides please contact your distributor agronomist.

Avoid prolonged contact of concentrate with metal sprayer parts. Undiluted Neutralize Tank Cleaner is not to be used on aluminium alloys, zinc or galvanised surfaces

5 L e

Rate of Use

Use 250 mL per 100 L of tank capacity.

Tank Capacity	250 Litres	500 Litres	1000 Litres	2000 Litres	5000 Litres
Quantity of NEUTRALIZE TANK CLEANER	0.625 Litres	1.25 Litres	2.5 Litres	5.0 Litres	12.5 Litres

Decontamination Procedure

1. Immediately after spraying, completely drain all equipment including tank, hoses and booms. Any contamination on the outside of the sprayer can be removed by washing with a solution of NEUTRALIZE TANK CLEANER and water (25ml in 10 L of water).
2. Rinse the inside of the tank with clean water to remove visible residues and flush through hoses and booms using at least 1/10 of the tanks capacity. Drain the tank completely including the sump.
3. Half fill the tank with clean water and add NEUTRALIZE TANK CLEANER at 250 mL per 100 L of the total capacity of the tank. Agitate and briefly flush the hoses and booms until the cleaning solution starts to come out through all the nozzles. Then completely fill the spray tank with water and allow to stand for 15 minutes with agitation running. Again flush the hoses and spray all of the solution out through the booms so that the tank is completely drained.

   Note: If it is not possible to completely drain the tank then step 3 should be repeated before moving to step 4.

4. Nozzles, non-drip diaphragms, screens and filters should be cleaned separately with a fresh solution of NEUTRALIZE TANK CLEANER and water (25mL in 10 L of water).
5. After following the NEUTRALIZE TANK CLEANER decontamination procedure, the tank should be rinsed with clean water and hoses and booms flushed through. The tank should be drained completely.
6. For the disposal of washings, follow the 'Code of Practice for using plant protection products' (DEFRA publications, 2006). Do not spray washings onto sensitive crops or land intended for imminent planting with sensitive crops.

BASF accept no liability for damage occurring as a result of failure to comply with instructions on this label.

Supplied by:
BASF plc
Crop Protection
PO Box 4, Earl Road
Cheadle Hulme, CHEADLE
Cheshire SK8 6QG
Tel: 0161 485 6222
Emergency Information:
(24 hours freephone):
0049 180 2273112
Technical Enquiries:
0845 602 2553 (office hours)

□·**BASF**

We create chemistry

® = Registered trademark of BASF

~xmam1487606187.indd   1   20.02.2017   16:56:31