

ml  
800  
  
700  
  
600  
  
500  
  
400  
  
300  
  
200  
ml

**BASF**  
We create chemistry

# Green Lawngrer®

## Turf paint and divot mix colourant

- Permanent green turf paint
- Improves appearance of damaged, dormant and stressed turf
- Produces uniform appearance to turf
- Turf preparation for high profile or media events
- Divot mix colourant
- Lasts up to 14 weeks
- May produce an allergic reaction. Contains: 1,2-benzisothiazol-3(2H)-one, formaldehyde

**Supplied by:**  
**BASF plc, 4th and 5th Floors, 2 Stockport Exchange, Railway Road, Stockport SK1 3GG, Telephone: 0161 475 3000**

**Emergency Information (24 hours freephone): 0049 180 227 3112**  
**Technical Enquiries: 0845 602 2553 (office hours)**

# 1 L

### APPLICATION RECOMMENDATION

Before applying Green Lawngrer®, mow turf area to desired height. 1L of Green Lawngrer covers between 0.01 – 0.03 hectares of turf. The wide coverage range is due to the type and condition of grass being treated, and turf colour desired. For application on dormant turf, dilute 1L of Green Lawngrer with 7 to 9 L of water. For a darker colour, a lower volume of water is recommended. Some experimentation may be required with ratios. For application on actively growing turf, dilute 1 L with 15 to 20 L of water. Rate depends on desired colour. For best results on discoloured areas, two applications perpendicular to one another are recommended to blend the applied area with the existing healthy turf. Green Lawngrer® can last for up to 14 weeks.

### Equipment Notice

BASF recommends the use of Teflon seals to aid in the prevention of leaks when using Green Lawngrer in centrifugal pumps. Standard ceramic seals may leak during operation. A spray shield is recommended for applications if overspray or drift is a potential problem. Avoid overspray on concrete, masonry, or any other objects where colour is not desired. Permanent staining may occur. Accidental overspray may be removed by a water rinse prior to drying. To prevent rub-off on clothing, allow Green Lawngrer to dry fully prior to using treated area. Rinse spray tank, spray nozzles, and screens thoroughly with water immediately following use. For best results, use low to medium sprayer pressure.

### Divot Mix Sand Colourant

Mix 200ml of Green Lawngrer with the same volume of water. Add the solution to 50 kg of divot mix sand in a cement-type mixer.

### CAUTION

Keep out of reach of children. Do not take internally. In case of eye contact, flush with large amounts of water and consult a physician. In case of ingestion, dilute with water or milk and consult a physician. Do not re-use this container. Rinse contents into the spray tank and crush prior to disposal. May produce an allergic reaction. Contains: 1,2-benzisothiazol-3(2H)-one, formaldehyde.

### WARRANTY DISCLAIMER:

BASF warrants that this product conforms to the description on the label and is reasonably fit for the purpose stated on the label when used in strict accordance with the directions. **BASF PLC DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

### REMEDIES:

The remedy for injury or damage from this product is limited to, in BASF plc sole discretion, replacement of the product or refund of the purchase price paid. **UNDER NO CIRCUMSTANCES SHALL BASF PLC BE LIABLE**

### LIMITATION OF LIABILITY:

No one is authorized to change or supplement, either verbally or in writing, the statements contained on the label. BASF plc and the seller are not liable for personal injury or property damage or loss, including crop damage or lack of performance, due to circumstances beyond their control, like a product user's failure to comply with the directions. Buyer and user assume all risks for these events.



® = Registered trademark of BASF  
81173331 GB 2123